

# MASTERFLEX® E/S®

## water sampling systems

### Portable Sampler

- Sample rate from 125 to 1100 mL/min; suction lift up to 26 feet
- IP54-rated when open or closed
- Variable-speed motor, reversible flow, and prime/purge function
- Run up to 4 hours on self-contained 12 VDC rechargeable battery, or indefinitely from AC or 12 VDC power supply (automotive, etc.)
- Comes complete with pump head, AC adapter with 12-ft cord, and 50 feet of High-Performance PVC tubing
- Dimensions: 41 x 29 x 27 cm (16"H x 11.3"W x 10.5"D). Weight: 7.5 kg (16.5 lb).



Portable sampler  
950-1990

### Ordering Information

Catalog number	Flow range	AC adapter voltage
VA-950-1990	125 to 1100 mL/min	115 VAC, 50/60 Hz
VA-950-1995	(1.98 to 17.4 GPH)	230 VAC, 50/60 Hz

Environmental Services Companies - Purchase this Sampling unit for water quality samples that meet EPA requirements for use of Peristaltic pumping technology

Basic unit pricing:

VA-950-1990 ..... \$ 1334.09 { price includes shipping via UPS Ground to locations in FLORIDA }  
Complete unit- Pump head, AC adapter with 12 foot cord and 50 feet of High Performance PVC tubing.